

1. IDENTIFICATION

Product Identifier: Epoxy Bonded Abrasive Products

Trade Name: Conventional Grinding Wheels or Stones with a Bond Specification "P"

Distributor Tyrolit Industrial Abrasives
6165 Kennedy Road,
Mississauga, ON, L5T 2S8
Canada

Phone Number (08:00-16:00): (905) 565-9880

Fax Number: (905) 565-9881

2. HAZARD(S) IDENTIFICATION

The hazard identification is based on a formalistic procedure as the hazard statements of the ingredients are summarized in section 3. This does not correspond to the hazardousness of the product itself.

A greater hazard, in most cases, is the exposure to the dust/fumes from the material or paint/coatings being ground. Most of the dust generated during grinding is from the base material being ground and the potential hazard from this exposure must be evaluated. This dust may present a fire or dust explosion hazard and may present a serious health hazard.

Classification:

Physical	Health	Environment
Not Hazardous	Specific Target Organ Toxicity – Repeated Exposure Category 1 Carcinogen Category 2	Not Hazardous

Hazards not otherwise classified: None

Symbol(s)



Signal word

Danger

Hazard statement(s)

H351 Suspected of causing cancer by inhalation.

H372 Causes damage to respiratory tract through prolonged or repeated inhalation.

Precautionary statement(s)

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust.

P264 Wash thoroughly after handling.

P281 Use personal protective equipment as required.

P270 Do not eat, drink or smoke when using this product.

P314 Get medical attention if you feel unwell.

P308+P313 If exposed or concerned: Get medical advice or

SDS03 - Safety Data Sheet

Epoxy Bonded Abrasive Products

attention.

P405 Store locked up.

P501 Dispose of contents in accordance with local, regional and national regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Mixtures:

Chemical name	CAS No.	Concentration
Aluminum Oxide	1344-28-1	≤95
Silicon Carbide	409-21-2	≤95
Kyanite	1302-76-7	≤22.7
Phenol Formaldehyde Polymer	9003-35-4	≤20
Cured epoxy resin	N/A	≤20
Calcium Oxide	1305-78-8	≤10
Ceramic Microspheres	N/A	≤10
Black Beauty	68476-96-0	≤9.1
Cryolite	15096-52-3	≤7.9
Calcium Carbonate	1317-65-3	≤5.6
Graphite	7782-42-5	≤1.2
Titanium Dioxide	13463-67-7	≤1%
The specific identity and/or exact percentage (concentration) of composition has been withheld as a trade secret and to cover products of variable composition. For more information about the composition for sampling purposes, contact Tyrolit Industrial Abrasives		

4. FIRST-AID MEASURES

Inhalation: If exposed to dust from grinding: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get immediate medical attention if breathing is difficult.

Skin contact: If contact with dust occurs, do not rub or scratch. Remove contaminated clothing. Rinse exposed skin with cold water then wash skin with soap and water. Get medical attention if irritation occurs. Launder clothing before re-use.

Eye contact: Flush eyes with large quantities of water, while holding the eyelids apart. Check victim for contact lenses and remove if possible while flushing. Get medical attention if irritation develops or persists. Get immediate medical attention for foreign body in eye.

Ingestion: If grinding dust is swallowed, seek medical attention.

Most important symptoms/effects, acute and delayed: May cause mechanical eye and skin irritation. Prolonged inhalation of dust or fumes from this product may cause perforation of the nasal septum and lung damage. This product contains titanium dioxide, which are suspected of causing cancer based on animal studies. Risk of cancer depends on duration and level of exposure. Exposure to dust generated from processing the base material or coatings may present additional health hazards.

Indication of immediate medical attention and special treatment, if necessary: Immediate medical attention is generally not required.

SDS03 - Safety Data Sheet

Epoxy Bonded Abrasive Products

5. FIRE-FIGHTING MEASURES

Suitable (and unsuitable) extinguishing media: Use any media that is appropriate for the surrounding materials.

Specific hazards arising from the chemical: This product is not combustible, however, consideration must be given to the potential fire or explosion hazards from the base material being processed. Many materials create flammable or explosive dusts or turnings when machined or ground.

Special protective equipment and precautions for fire-fighters: Firefighters should wear full emergency equipment and NIOSH approved positive pressure self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures: Wear appropriate respirator and personal protective equipment as needed to avoid eye contact, skin contact and to prevent inhalation of dust.

Environmental precautions: Avoid contamination of water supplies and environmental releases. Report spills as required to authorities.

Methods and materials for containment and cleaning up: Carefully collect dry material, avoiding the creation of airborne dust. Place in a suitable container for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling: Do not breathing dust. Use with adequate ventilation. Avoid eye and skin contact with grinding dust. Wear suitable gloves, eye protection and appropriate protective clothing according to the operation. Wash thoroughly after handling. Consider potential exposure to components of the base materials or coatings being ground. Refer to OSHA's substance specific standards for additional work practice requirements where applicable.

Conditions for safe storage, including any incompatibilities: Store in accordance with ANSI B7.1. Protect abrasive wheels from damage.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure guidelines:

Aluminum Oxide	15 mg/m3 TWA OSHA PEL (total dust) 5 mg/m3 TWA OSHA PEL (respirable fraction)
Silicon Carbide	0.1 mg/m3 f/cc(F) TWA ACGIH TLV (including whiskers) 15 mg/m3 TWA OSHA PEL (total dust) 5 mg/m3 TWA OSHA PEL (respirable fraction)
Kyanite	None Established
Phenol Formaldehyde Polymer	None Established
Cured epoxy resin	None Established
Calcium Oxide	2 mg/m3 TWA ACGIH TLV 5 mg/m3 TWA OSHA PEL
Ceramic Microspheres	None Established
Black Beauty	None Established
Cryolite	None Established
Calcium Carbonate	15 mg/m3 TWA OSHA PEL (total dust)

SDS03 - Safety Data Sheet

Epoxy Bonded Abrasive Products

	5 mg/m ³ TWA OSHA PEL (respirable fraction)
Graphite	2 mg/m ³ TWA ACGIH TLV (respirable) 15 mppcf mg/m ³ TWA OSHA PEL (based on impinger samples counted by light field technologies)
Titanium Dioxide	10 mg/m ³ TWA ACGIH TLV 15 mg/m ³ TWA OSHA PEL (total dust)
Formaldehyde*	0.1 ppm TWA ACGIH TLV, 0.3 ppm STEL ACGIH TLV 0.2 0.75 ppm TWA OSHA PEL, 2 ppm STEL OSHA PEL

*Product may release formaldehyde during use.

Appropriate engineering controls: Use local exhaust or general ventilation as required to minimize exposure to dust and maintain the concentration of contaminants below the TLVs.

Individual protection measures, such as personal protective equipment:

Respiratory protection: Use NIOSH approved respirator if exposure limits are exceeded or where dust exposures are excessive. Consider the potential for exposure to components of the coatings or base material being ground in selecting proper respiratory protection. Refer to OSHA's specific standards for lead, cadmium, etc. where appropriate. Selection of respiratory protection depends on the contaminant type, form and concentration. Select and use respirators in accordance with OSHA 1910.134 and good industrial hygiene practice.

Skin protection: Cloth or leather gloves recommended.

Eye protection: Safety goggles or face shield over safety glasses with side shields.

Other: Protective clothing as needed to prevent contamination of personal clothing. Hearing protection may be required.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.): Solid grinding wheel or stone of various colors.

Odor: No Odor

Odor threshold: Not applicable	pH: 7.1 (10% solution in water)
Melting point/freezing point: Not applicable	Initial boiling point and boiling range: Not applicable
Flash point: Non-Combustible	Evaporation rate: Not applicable
Flammability (solid, gas): Not applicable	UEL: Not applicable
Flammable limits: LEL: Not applicable	Vapor density:
Vapor pressure: Not applicable	Solubility(ies): Very slightly
Relative density: 1.5-3.1	Auto-ignition temperature: Not applicable
Partition coefficient: n-octanol/water: Not applicable	Viscosity: Not applicable
Decomposition temperature: Not applicable	

10. STABILITY AND REACTIVITY

Reactivity: Not reactive

Chemical stability: Stable

Possibility of hazardous reactions: Will not occur.

Conditions to avoid: None known

Incompatible materials: Strong acids and bases.

Hazardous decomposition products: Dust from grinding could contain ingredients listed in Section 3 and other, potentially more hazardous components of the base material being ground or coatings applied to the base material.

SDS03 - Safety Data Sheet

Epoxy Bonded Abrasive Products

11. TOXICOLOGICAL INFORMATION

Likely routes of exposure:

Inhalation: Dust may cause respiratory irritation.

Ingestion: None expected under normal use conditions. Swallowing large pieces may cause obstruction of the gastrointestinal tract.

Skin contact: None expected under normal use conditions. Rubbing product across the skin may cause mechanical irritation or abrasions.

Eye contact: Dust may cause mechanical eye irritation.

Chronic effects from short- and long-term exposure: Long-term overexposure to respirable dust may cause lung damage (fibrosis) with symptoms of coughing, shortness of breath and diminished breathing capacity. Risk of cancer depends on the level and duration of exposure. Chronic effects may be aggravated by smoking. Prolonged exposure to elevated noise levels during operations may affect hearing. A greater hazard, in most cases, is the exposure to the dust/fumes from the material or paint/coatings being ground. Most of the dust generated during grinding is from the base material being ground and the potential hazard from this exposure must be evaluated.

Numerical measures of toxicity: This product and its components are not acutely toxic. The only acute toxicity data available for the components are listed below.

Aluminum Oxide: LD50 Oral rat >5,000 mg/kg

Cryolite: LD50 Oral rat >5,000 mg/kg

Graphite: LD50 oral rat > 2000 mg/kg, LC50 inhalation rat > 2 mg/L

Carcinogenicity: Titanium dioxide is listed by IARC as a group 2B carcinogen (possible human carcinogen). None of the other components in this product are listed as a carcinogen or potential carcinogen by OSHA, NTP, IARC, or the EU CLP.

12. ECOLOGICAL INFORMATION

Ecotoxicity:

Graphite: Danio rerio LC50 > 100 mg/L/96hr

Persistence and degradability: Biodegradation is not applicable to inorganic compounds.

Bioaccumulative potential: No data available

Mobility in soil: No data available.

Other adverse effects: No data available.

13. DISPOSAL CONSIDERATIONS

Dispose in accordance with all applicable local, state/provincial and federal regulations. Local regulations may be more stringent than regional and national requirements. It is the responsibility of the waste generator to determine the toxicity and physical characteristics of the material to determine the proper waste identification and disposal in compliance with applicable regulations.

14. TRANSPORT INFORMATION

	UN Number	Proper shipping name	Hazard Class	Packing Group	Environmental Hazard
DOT	None	Not Regulated	None	None	None
TDG	None	Not Regulated	None	None	None

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not applicable – product is transported only in packaged form.

SDS03 - Safety Data Sheet

Epoxy Bonded Abrasive Products

Special precautions: None identified.

15. REGULATORY INFORMATION

SARA Section 311/312 Hazard Categories: Not Applicable (manufactured articles)

SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372 (Toxic Chemical Release Reporting):

Components	C.A.S. #	WT %
None		

California Proposition 65: WARNING You create dust when you cut, sand, drill or grind materials such as wood, paint, cement, masonry or metal. This dust often contains chemicals known to cause cancer, birth defects or other reproductive harm.

This SDS has been prepared in accordance with US OSHA HazCom 2012 and Canadian WHMIS 2015 regulations.

16. OTHER INFORMATION

NFPA Rating: Health = 0 Flammability = 0 Instability = 0
HMIS Rating: Health = 0* Flammability = 0 Physical Hazard = 0
*Chronic health hazard

Date of Revision: 06/29/2022

Reviewed: 06/29/2022

The information and recommendations set forth are taken from sources believed to be accurate. Radiac Abrasives, Inc., A Tyrolit Company, makes no warranty with respect to the accuracy of this information or the suitability of these recommendations, assumes no liability to any user thereof. It is the responsibility of the user to investigate and understand pertinent sources of information to comply with all laws and procedures applicable to the safe use and handling of the product and to determine the suitability of the product for its intended use.

SDS03 - Safety Data Sheet
Epoxy Bonded Abrasive Products

Epoxy Bonded Abrasive Products

Produits abrasifs à liant époxy

DANGER



DANGER

Hazard statement(s)

H351 Suspected of causing cancer by inhalation.
H372 Causes damage to respiratory tract through prolonged or repeated inhalation.

Precautionary statement(s)

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust.
P264 Wash thoroughly after handling.
P281 Use personal protective equipment as required.
P270 Do not eat, drink or smoke when using this product. P314 Get medical attention if you feel unwell.
P308+P313 If exposed or concerned: Get medical advice or attention.
P405 Store locked up.
P501 Dispose of contents in accordance with local, regional and national regulations.

Store only in original packaging.

Tyrolit Industrial Abrasives
6165 Kennedy Road,
Mississauga, ON, L5T 2S8
Canada
Phone number: (905) 565-9880

Mention(s) de danger

H351 Susceptible de provoquer le cancer par inhalation.
H372 Provoque des dommages aux voies respiratoires suite à des inhalations prolongées ou répétées.

Mise(s) en garde

P201 Obtenir des instructions spéciales avant l'utilisation.
P202 Ne pas manipuler jusqu'à ce que toutes les précautions de sécurité ont été lues et comprises.
P260 Ne pas respirer les poussières.
P264 Bien laver après manipulation.
P281 Utiliser l'équipement de protection personnelle, le cas échéant.
P270 Ne pas manger, boire ou fumer en manipulant ce produit.
P314 Consulter un médecin en cas de malaise.
P308+P313 En cas d'exposition ou de préoccupations, consulter un médecin.
P405 Garder sous clé.
P501 Éliminer le contenu en accord avec les réglementations locales, régionales et nationales.

Conserver uniquement dans l'emballage d'origine.