

1. IDENTIFICATION**Product identifier:** Metal Bonded Products**Trade Name:** Grinding Wheels or Stones**Distributor** Tyrolit Industrial Abrasives
6165 Kennedy Road,
Mississauga, ON, L5T 2S8
Canada**Phone Number (08:00-16:00):** (905) 565-9880**Fax Number:** (905) 565-9881**2. HAZARD(S) IDENTIFICATION**

The hazard identification is based on a formalistic procedure as the hazard statements of the ingredients are summarized in section 3. This does not correspond to the hazardousness of the product itself.

A greater hazard, in most cases, is the exposure to the dust/fumes from the material or paint/coatings being ground. Most of the dust generated during grinding is from the base material being ground and the potential hazard from this exposure must be evaluated. This dust may present a fire or dust explosion hazard and may present a serious health hazard.

Classification:

Physical	Health	Environment
Not Hazardous	Acute Toxicity Category 4 (oral) Carcinogen Category 1B Reproductive Toxicity Category 2 (fertility) Skin Sensitization Category 1 Respiratory Sensitization Category 1	Not Hazardous

Hazards not otherwise classified: None**Symbol(s)****Signal word**

Danger!

Hazard statement(s)

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H350 May cause cancer by inhalation.

H361 Suspected of damaging fertility.

SDS11 – Revision 06/29/2022

Precautionary statement(s)

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing dust or fumes.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

SDS11 - Safety Data Sheet

Metal Bonded Products

P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves.
P281 Use personal protective equipment as required.
P285 In case of inadequate ventilation wear respiratory protection.
P301 + P312 IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.
P330 Rinse mouth.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P333+P313 If skin irritation or rash occurs: Get medical attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P304 + P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor.
P308 + P313 If exposed or concerned: Get medical attention.
P405 Store locked up.
P501 Dispose of contents and container in accordance with local and national regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Mixtures:

Chemical name	CAS No.	Concentration
Cobalt	7440-48-4	≤100%
Copper	7440-50-8	≤100%
Tin	7440-31-5	≤100%
Silver	7440-22-4	≤70%
Graphite	7782-42-5	≤35%
The specific identity and/or exact percentage (concentration) of composition has been withheld as a trade secret and to cover products of variable composition. For more information about the composition for sampling purposes, contact Tyrolit Industrial Abrasives.		

4. FIRST-AID MEASURES

Inhalation: Remove victim to fresh air. If irritation or other symptoms persist, get medical attention. If asthma-like symptoms or difficulty breathing occur, get immediate medical attention.

Skin contact: No first aid should be required. Remove contaminated clothing. Rinse exposed skin with cold water then wash skin with soap and water. Get medical attention if irritation or rash occurs. Launder clothing before re-use.

Eye contact: Flush eyes with large quantities of water, while holding the eyelids apart. Get medical attention if irritation develops or persists.

Ingestion: Not an anticipated route of exposure. If swallowed, drink 1 or 2 glasses of water to dilute. Never give anything by mouth to an unconscious or convulsing person. Get medical attention.

Most important symptoms/effects, acute and delayed: Dust may cause mechanical eye, skin and respiratory irritation. Dust particles may cause abrasive injury to the eyes. May cause skin sensitization (allergic reaction). May cause respiratory

SDS11 – Revision 06/29/2022

SDS11 - Safety Data Sheet

Metal Bonded Products

sensitization with asthma-like symptoms and difficulty breathing. Inhalation of fumes may cause metal fume fever with flu-like symptoms. Prolonged inhalation of dust or fumes from this product may cause perforation of the nasal septum and damage to the lungs. This product contains cobalt, which may cause cancer based on animal studies. Risk of cancer depends on duration and level of exposure. Cobalt is also suspected of damaging fertility in males.

Indication of immediate medical attention and special treatment, if necessary: Immediate medical attention is required if asthma-like symptoms occur or breathing is difficult.

5. FIRE-FIGHTING MEASURES

Suitable (and unsuitable) extinguishing media: Use any media that is appropriate for the surrounding materials.

Specific hazards arising from the chemical: This product is not combustible; however, consideration must be given to the potential fire or explosion hazards from the base material being processed. Many materials create flammable or explosive dusts or turnings when machined or ground. Toxic metal fumes and oxides are emitted when product is heated above the metal point.

Special protective equipment and precautions for fire-fighters: Firefighters should wear full emergency equipment and NIOSH approved positive pressure self-contained breathing apparatus. Contain water used in firefighting from entering sewers or natural waterways.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures: Wear appropriate respirator and protective clothing as needed to prevent eye contact and inhalation of dust or fumes.

Environmental precautions: Avoid contamination of water supplies and environmental releases. Report spills as required to authorities. Prevent release to the environment.

Methods and materials for containment and cleaning up: Carefully collect dry material, avoiding the creation of airborne dust. Place in a suitable container for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling: Do not breathe dust. Use with adequate ventilation. Avoid eye and skin contact with grinding dust. Wear suitable gloves, eye protection and appropriate protective clothing according to the operation. Wash thoroughly after handling. Consider potential exposure to components of the base materials or coatings being ground. Refer to OSHA's substance specific standards for additional work practice requirements where applicable.

Conditions for safe storage, including any incompatibilities: Store in accordance with ANSI B7.1. Protect abrasive wheels from damage.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure guidelines:

Cobalt	0.02 mg/m ³ TWA ACGIH TLV 0.1 mg/m ³ TWA OSHA PEL (dust and fume)
Copper	1 mg/m ³ TWA ACGIH TLV (as dust) 1 mg/m ³ TWA OSHA PEL (as dust)

SDS11 - Safety Data Sheet

Metal Bonded Products

	0.2 mg/m ³ TWA ACGIH TLV (as fume) 0.1 mg/m ³ TWA OSHA PEL (as fume)
Tin	2 mg/m ³ TWA ACGIH TLV 2 mg/m ³ TWA OSHA PEL
Silver (metal)	0.1 mg/m ³ TWA ACGIH TLV (dust and fume) 0.01 mg/m ³ TWA OSHA PEL
Graphite	2 mg/m ³ TWA ACGIH TLV (Respirable) 15 mg/m ³ TWA OSHA PEL (Total dust) 5 mg/m ³ TWA OSHA PEL (Respirable)

Appropriate engineering controls: Use local exhaust or general ventilation as required to minimize exposure to dust and maintain the concentration of contaminants below the TLVs.

Individual protection measures, such as personal protective equipment:

Respiratory protection: Use NIOSH approved respirator if exposure limits are exceeded or where dust exposures are excessive. Consider the potential for exposure to components of the coatings or base material being ground in selecting proper respiratory protection. Refer to OSHA's specific standards for lead, cadmium, etc. where appropriate. Selection of respiratory protection depends on the contaminant type, form and concentration. Select and use respirators in accordance with OSHA 1910.134 and good industrial hygiene practice.

Skin protection: Impervious gloves recommended.

Eye protection: Safety goggles recommended.

Other: Protective clothing as needed to prevent contamination of personal clothing. Hearing protection may be required.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.): Solid of various colors.

Odor: May give off odor during use.

Odor threshold: Not applicable	pH: Not applicable
Melting point/freezing point: Not applicable	Initial boiling point and boiling range: Not applicable
Flash point: Non-Combustible	Evaporation rate: Not applicable
Flammability (solid, gas): Not applicable	UEL: Not applicable
Flammable limits: LEL: Not applicable	Vapor density:
Vapor pressure: Not applicable	Solubility(ies): Very slightly
Relative density: Not determined	Auto-ignition temperature: Not applicable
Partition coefficient: n-octanol/water: Not applicable	Viscosity: Not applicable
Decomposition temperature: Not applicable	

10. STABILITY AND REACTIVITY

Reactivity: Not reactive

Chemical stability: Stable

Possibility of hazardous reactions: None known.

Conditions to avoid: None known

Incompatible materials: None known.

Hazardous decomposition products: Dust from grinding could contain ingredients listed in Section 3 and other, potentially more hazardous components of the base material being ground or coatings applied to the base material. Toxic metal fumes and oxides are emitted when product is heated above the metal point.

SDS11 - Safety Data Sheet

Metal Bonded Products

11. TOXICOLOGICAL INFORMATION

Likely routes of exposure:

Inhalation: Dust generated from processing may cause respiratory irritation. Inhalation of fumes may cause metal fume fever, which is characterized by flu-like symptoms with metallic taste, fever, chills, chest pain, and fatigue and muscle pain. Symptoms generally resolve in 24-48 hours. May cause allergic respiratory response with asthma-like symptoms and difficulty breathing. Respiratory sensitization may be life-threatening.

Ingestion: None expected under normal use conditions. Swallowing large pieces may cause obstruction of the gastrointestinal tract.

Skin contact: Dust generated from processing may cause abrasive irritation. May cause allergic skin reaction (sensitization).

Eye contact: Contact with dust particles may cause abrasive injury to the eyes.

Chronic effects from short- and long-term exposure: Long-term overexposure to respirable dust may cause lung damage (fibrosis) with symptoms of coughing, shortness of breath and diminished breathing capacity. Most of the dust generated during grinding is from the base material being ground and the potential hazard from this exposure must be evaluated. Cobalt is suspected of damaging fertility in males. Chronic effects may be aggravated by smoking. Prolonged exposure to elevated noise levels during operations may affect hearing. A greater hazard, in most cases, is the exposure to the dust/fumes from the material or paint/coatings being ground.

Numerical measures of toxicity:

Cobalt: Oral rat LD50 550 mg/kg

Copper: Oral rat LD50 > 2500 mg/kg, inhalation rat LC50 > 5.11 mg/L, dermal rat LD50 > 2000 mg/kg

Tin: Oral rat LD50->2000 mg/kg; Inhalation rat LC50->4.75 mg/L/4hr (no mortalities); Skin rat LD50->2000 mg/kg

Silver: Oral rat LD50->5000 mg/kg; Skin rat LD50 - >2000 mg/kg

Graphite: Oral rat LD50 > 2000 mg/kg, inhalation rat LC50 > 2 mg/L

Carcinogenicity: This product contains cobalt, which is classified by IARC as Possibly Carcinogenic to Humans (Category 2B) and by NTP as Reasonably Anticipated to Be Carcinogenic to Humans. None of the other components are listed as a carcinogen or potential carcinogen by OSHA, NTP or IARC.

12. ECOLOGICAL INFORMATION

Ecotoxicity:

Cobalt: 96 hr LC50 Brachydanio rerio->100 mg/L; 48 hr Daphnia magna- NOEC- 3.2 mg/L; 72 hr Selenastrum capricornutum (algae) – NOEC – 0.01-0.015 mg/L

Copper: 96 hr LC50 Rainbow trout – 190-210 ug/L; 96 hr LC50 Fathead minnow- 390 ug/L; 48 hr LC50 Daphnia magna- 33.8-792 ug/L

Silver: 96 hr LC50 Fathead minnow-1.2 ug/L; 48 hr LC50 Daphnia magna- 0.22 ug/L (M-Factor Acute: 1, M-Factor Chronic: 10)

This product is a metal in a massive form. The components are not available in the aquatic environment. No environmental hazards are expected from the solid form of this product as sold and transported.

Persistence and degradability: Biodegradation is not applicable to inorganic compounds.

Bioaccumulative potential: No data available

Mobility in soil: No data available.

Other adverse effects: No data available.

13. DISPOSAL CONSIDERATIONS

Dispose in accordance with all applicable local, state/provincial and federal regulations. Local regulations may be more stringent than regional and national requirements. It is the responsibility of the waste generator to determine the toxicity and

SDS11 – Revision 06/29/2022

SDS11 - Safety Data Sheet

Metal Bonded Products

physical characteristics of the material to determine the proper waste identification and disposal in compliance with applicable regulations.

14. TRANSPORT INFORMATION

	UN Number	Proper shipping name	Hazard Class	Packing Group	Environmental Hazard
DOT	None	Not Regulated	None	None	None
TDG	None	Not Regulated	None	None	None

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not applicable – product is transported only in packaged form.

Special precautions: None identified.

15. REGULATORY INFORMATION

SARA Section 311/312 Hazard Categories: Not Applicable (manufactured articles)

SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372 (Toxic Chemical Release Reporting):

Components	C.A.S. #	WT %
Cobalt	7440-48-4	≤100%
Copper	7440-50-8	≤30%
Silver	7440-22-4	≤70%

California Proposition 65: WARNING You create dust when you cut, sand, drill or grind materials such as wood, paint, cement, masonry or metal. This dust often contains chemicals known to cause cancer, birth defects or other reproductive harm.

Canada: This product has been classified under the CPR and this SDS discloses information elements required by the CPR.

16. OTHER INFORMATION

NFPA Rating: Health = 2 Flammability = 0 Instability = 0
HMIS Rating: Health = 2* Flammability = 0 Physical Hazard = 0
*Chronic Health Hazard

Date of Revision: 06/29/2022

Reviewed: 06/29/2022

The information and recommendations set forth are taken from sources believed to be accurate. Radiac Abrasives, Inc., a Tyrolit Company, makes no warranty with respect to the accuracy of this information or the suitability of these recommendations, assumes no liability to any user thereof. It is the responsibility of the user to investigate and understand pertinent sources of information to comply with all laws and procedures applicable to the safe use and handling of the product and to determine the suitability of the product for its intended use.

SDS11 - Safety Data Sheet
Metal Bonded Products

Metal Bonded Products

DANGER



Hazard statement(s)

H302 Harmful if swallowed.
H317 May cause an allergic skin reaction.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H350 May cause cancer by inhalation.
H361 Suspected of damaging fertility.

Precautionary statement(s)

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P261 Avoid breathing dust or fumes.
P264 Wash thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves.
P281 Use personal protective equipment as required.
P285 In case of inadequate ventilation wear respiratory protection.
P301 + P312 IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.
P330 Rinse mouth.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P333+P313 If skin irritation or rash occurs: Get medical attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P304 + P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor.
P308 + P313 If exposed or concerned: Get medical attention.
P405 Store locked up.
P501 Dispose of contents and container in accordance with local and national regulations.

Store only in original packaging.

Tyrolit Industrial Abrasives
6165 Kennedy Road,
Mississauga, ON, L5T 2S8
Canada
Phone number: (905) 565-9880

SDS11 – Revision 06/29/2022

Produits à liant métallique

DANGER

Mention(s) de danger

H302 Nocif en cas d'ingestion.
H317 Peut provoquer une allergie cutanée.
H334 Peut provoquer des symptômes allergiques ou d'asthme ou des difficultés respiratoires par inhalation.
H350 Peut provoquer le cancer
H361 Susceptible de nuire à la fertilité ou au fœtus

Mise(s) en garde

P201 Obtenir des instructions spéciales avant l'utilisation.
P202 Ne pas manipuler jusqu'à ce que toutes les précautions de sécurité aient été lues et comprises.
P261 Éviter de respirer les poussières ou fumées.
P264 Bien laver après manipulation.
P270 Ne pas manger, boire ou fumer en manipulant ce produit.
P272 Les vêtements de travail contaminés ne devraient pas être autorisés à sortir de leur lieu de travail.
P280 Porter des gants, vêtements de protection et lunettes de sécurité.
P281 Utiliser l'équipement de protection individuel requis.
P285 Lorsque la ventilation du local est insuffisante, porter un équipement de protection respiratoire.
P301 + P312 EN CAS D'INGESTION: appeler un CENTRE ANTIPOISON/un médecin/.../en cas de malaise.
P330 Rincer la bouche.
P302 +P352 En cas de contact avec la peau, laver abondamment avec de l'eau.
P333+P313 En cas d'irritation de la peau, consulter un médecin.
P362+P364 Retirer les vêtements contaminés et les laver avant de les porter de nouveau.
P308+P313 En cas d'exposition ou de préoccupations, consulter un médecin.
P405 Garder sous clé.
P501 Éliminer le contenu et le contenant en accord avec les réglementations locales et nationales.

Conserver uniquement dans l'emballage d'origine.