

**1. IDENTIFICATION****Product identifier:** Vitrified Bonded Abrasive Products**Trade Name:** Grinding Wheels or Stones with a Specification Bond Marking "V"**Manufacturer/** Radiac Abrasives, Inc.**Distributor** A Tyrolit Company  
1015 S. College Avenue  
P.O. Box 1410  
Salem, IL 62881**Phone Number (08:00 – 16:00):** (800) 851-1095**Fax Number:** (888) 244-8234**2. HAZARD(S) IDENTIFICATION**

The hazard identification is based on a formalistic procedure as the hazard statements of the ingredients are summarized in section 3. This does not correspond to the hazardousness of the product itself.

A greater hazard, in most cases, is the exposure to the dust/fumes from the material or paint/coatings being ground. Most of the dust generated during grinding is from the base material being ground and the potential hazard from this exposure must be evaluated. This dust may present a fire or dust explosion hazard and may present a serious health hazard.

**Classification:**

Physical	Health	Environment
Not Hazardous	Skin Irritant Category 2 Carcinogen Category 1	Not Hazardous

**Hazards not otherwise classified:** None**Symbol(s)****Signal word**

Danger!

**Hazard statement(s)**

H315 Causes skin irritation

H350 May cause cancer by inhalation.

**Precautionary statement(s)**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P264 Wash thoroughly after handling.

P280 Wear protective gloves.

P308 + P313 If exposed or concerned: Get medical attention.

P302+P352 IF ON SKIN: Wash with plenty of water.

P332+P313 If skin irritation occurs: Get medical attention.

# SDS06 - Safety Data Sheet

## Vitrified Bonded Abrasive Products

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents and container in accordance with local and national regulations.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

#### Mixtures:

Chemical name	CAS No.	Concentration
Aluminum Oxide	1344-28-1	≤95%
Silicon Carbide	409-21-2	≤95%
Glass or Glass/Porcelain	NA	≤40%
Titanium Dioxide	13463-67-7	≤1%
Quartz Silica	14808-60-7	≤1%
<b>May contain one of the following treatments:</b>		
Sulfur	7704-34-9	≤35%
Paraffin	NA	≤35%
Resin	NA	≤35%
The specific identity and/or exact percentage (concentration) of composition has been withheld as a trade secret and to cover products of variable composition. For more information about the composition for sampling purposes, contact Radiac Abrasives.		

### 4. FIRST-AID MEASURES

**Inhalation:** If exposed to dust from grinding: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get immediate medical attention if breathing is difficult.

**Skin contact:** Wash dust from skin with soap and water for several minutes. If irritation occurs, get medical attention. Launder contaminated clothing before reuse.

**Eye contact:** Do not rub. Flush eyes thoroughly with plenty of water, holding open eyelids. Get medical attention if irritation persists. Obtain immediate medical attention for foreign body in the eye.

**Ingestion:** If grinding dust is swallowed, seek medical attention.

**Most important symptoms/effects, acute and delayed:** Contact with dust may cause eye and skin irritation. Prolonged overexposure to respirable crystalline silica causes lung disease (silicosis) and increases the risk of lung cancer. This product contains titanium dioxide, which is suspected of causing cancer based on animal studies. Risk of cancer depends on duration and level of exposure.

**Indication of immediate medical attention and special treatment, if necessary:** Immediate medical attention is generally not required.

### 5. FIRE-FIGHTING MEASURES

**Suitable (and unsuitable) extinguishing media:** Use any media that is appropriate for the surrounding materials.

## SDS06 - Safety Data Sheet

### Vitrified Bonded Abrasive Products

**Specific hazards arising from the chemical:** This product is not combustible; however, consideration must be given to the potential fire or explosion hazards from the base material being processed. Many materials create flammable or explosive dusts or turnings when machined or ground.

**Special protective equipment and precautions for fire-fighters:** Firefighters should wear full emergency equipment and NIOSH approved positive pressure self-contained breathing apparatus.

#### 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment, and emergency procedures:** Wear appropriate respirator and protective clothing as needed to avoid eye contact and inhalation of dust.

**Environmental precautions:** Avoid contamination of water supplies and environmental releases. Report spills as required to authorities.

**Methods and materials for containment and cleaning up:** Carefully collect dry material, avoiding the creation of airborne dust. Place in a suitable container for disposal.

#### 7. HANDLING AND STORAGE

**Precautions for safe handling:** Avoid breathing dust. Use with adequate ventilation. Avoid eye and skin contact with grinding dust. Wear suitable gloves, eye protection and appropriate protective clothing according to the operation. Wash thoroughly after handling. Consider potential exposure to components of the base materials or coatings being ground. Refer to OSHA's substance specific standards for additional work practice requirements where applicable.

**Conditions for safe storage, including any incompatibilities:** Store in accordance with ANSI B7.1. Protect abrasive wheels from damage.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Exposure guidelines:**

Aluminum Oxide	15 mg/m <sup>3</sup> TWA OSHA PEL (total dust) 5 mg/m <sup>3</sup> TWA OSHA PEL (respirable fraction)
Silicon Carbide	0.1 mg/m <sup>3</sup> f/cc(F) TWA ACGIH TLV (including whiskers) 15 mg/m <sup>3</sup> TWA OSHA PEL (total dust) 5 mg/m <sup>3</sup> TWA OSHA PEL (respirable fraction)
Glass or Glass/Porcelain	None Established
Titanium Dioxide	10 mg/m <sup>3</sup> TWA ACGIH TLV 15 mg/m <sup>3</sup> TWA OSHA PEL (total dust)
Quartz Silica	0.025 mg/m <sup>3</sup> TWA ACGIH TLV (respirable fraction), 0.05 mg/m <sup>3</sup> TWA OSHA PEL
Sulfur	None Established
Paraffin	None Established
Resin	None Established

**Appropriate engineering controls:** Use local exhaust or general ventilation as required to minimize exposure to dust and maintain the concentration of contaminants below the TLVs.

**Individual protection measures, such as personal protective equipment:**

# SDS06 - Safety Data Sheet

## Vitrified Bonded Abrasive Products

**Respiratory protection:** Use NIOSH approved respirator if exposure limits are exceeded or where dust exposures are excessive. Consider the potential for exposure to components of the coatings or base material being ground in selecting proper respiratory protection. Refer to OSHA's specific standards for lead, cadmium, etc. where appropriate. Selection of respiratory protection depends on the contaminant type, form and concentration. Select and use respirators in accordance with OSHA 1910.134 and good industrial hygiene practice.

**Skin protection:** Cloth or leather gloves recommended.

**Eye protection:** Safety goggles or face shield over safety glasses with side shields.

**Other:** Protective clothing as needed to prevent contamination of personal clothing. Hearing protection may be required.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance (physical state, color, etc.):** Solid Wheel or stone of various colors.

**Odor:** No Odor

<b>Odor threshold:</b> Not applicable	<b>pH:</b> Not applicable
<b>Melting point/freezing point:</b> Not applicable	<b>Initial boiling point and boiling range:</b> Not applicable
<b>Flash point:</b> Non-Combustible	<b>Evaporation rate:</b> Not applicable
<b>Flammability (solid, gas):</b> Not applicable	<b>UEL:</b> Not applicable
<b>Flammable limits: LEL:</b> Not applicable	<b>Vapor density:</b>
<b>Vapor pressure:</b> Not applicable	<b>Solubility(ies):</b> Very slightly
<b>Relative density:</b> 1.5-3.1	<b>Auto-ignition temperature:</b> Not applicable
<b>Partition coefficient: n-ctanol/water:</b> Not applicable	<b>Viscosity:</b> Not applicable
<b>Decomposition temperature:</b> Not applicable	

### 10. STABILITY AND REACTIVITY

**Reactivity:** Not reactive

**Chemical stability:** Stable

**Possibility of hazardous reactions:** Will not occur.

**Conditions to avoid:** None known

**Incompatible materials:** Strong acids and bases

**Hazardous decomposition products:** Dust from grinding could contain ingredients listed in Section 3 and other, potentially more hazardous components of the base material being ground or coatings applied to the base material.

### 11. TOXICOLOGICAL INFORMATION

**Likely routes of exposure:**

**Inhalation:** Inhalation of dust may cause irritation to the nose, throat and upper respiratory tract with coughing and shortness of breath.

**Ingestion:** None expected under normal use conditions. Swallowing large pieces may cause obstruction of the gastrointestinal tract.

**Skin contact:** Contact with dust may cause skin irritation.

**Eye contact:** Dust particles may cause abrasive injury to the eyes.

**Chronic effects from short- and long-term exposure:** Long-term overexposure to respirable dust may cause lung damage (fibrosis) with symptoms of coughing, shortness of breath and diminished breathing capacity. Prolonged inhalation of respirable crystalline silica may cause lung disease and cancer. Risk of cancer depends on the level and duration of exposure. Chronic effects may be aggravated by smoking. Prolonged exposure to elevated noise levels during operations may affect hearing. A greater hazard, in most cases, is the exposure to the dust/fumes from the material or paint/coatings

## SDS06 - Safety Data Sheet

### Vitrified Bonded Abrasive Products

being ground. Most of the dust generated during grinding is from the base material being ground and the potential hazard from this exposure must be evaluated.

**Numerical measures of toxicity:** This product and its components are not acutely toxic.

**Carcinogenicity:** Titanium dioxide is listed by IARC as a group 2B carcinogen (possible human carcinogen). Crystalline silica quartz is listed as "Carcinogenic to Humans" (Group 1) by IARC, "Known to be a Human Carcinogen" by NTP, as is an OSHA Listed Carcinogen. None of the other components are listed as a carcinogen or potential carcinogen by OSHA, NTP, IARC, or the EU CLP.

#### 12. ECOLOGICAL INFORMATION

**Ecotoxicity:** No data available.

**Persistence and degradability:** Biodegradation is not applicable to inorganic compounds.

**Bioaccumulative potential:** No data available

**Mobility in soil:** No data available.

**Other adverse effects:** No data available.

#### 13. DISPOSAL CONSIDERATIONS

Dispose in accordance with all applicable local, state/provincial and federal regulations. Local regulations may be more stringent than regional and national requirements. It is the responsibility of the waste generator to determine the toxicity and physical characteristics of the material to determine the proper waste identification and disposal in compliance with applicable regulations.

#### 14. TRANSPORT INFORMATION

	UN Number	Proper shipping name	Hazard Class	Packing Group	Environmental Hazard
<b>DOT</b>	None	Not Regulated	None	None	None
<b>TDG</b>	None	Not Regulated	None	None	None

**Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Not applicable – product is transported only in packaged form.

**Special precautions:** None identified.

#### 15. REGULATORY INFORMATION

**SARA Section 311/312 Hazard Categories:** Not Applicable (manufactured articles)

**SARA Section 313:** This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372 (Toxic Chemical Release Reporting):

Components	C.A.S. #	WT %
None		

## SDS06 - Safety Data Sheet

### Vitrified Bonded Abrasive Products

**California Proposition 65:** WARNING You create dust when you cut, sand, drill or grind materials such as wood, paint, cement, masonry or metal. This dust often contains chemicals known to cause cancer, birth defects or other reproductive harm.

This product has been classified under the CPR and this SDS discloses information elements required by the CPR.

<b>16. OTHER INFORMATION</b>
------------------------------

<b>NFPA Rating:</b> Health = 1	Flammability = 0	Instability = 0
<b>HMIS Rating:</b> Health = 1	Flammability = 0	Physical Hazard = 0

**Date of current revision:** 03/13/2018

The information and recommendations set forth are taken from sources believed to be accurate. Radiac Abrasives, Inc., a Tyrolit Company, makes no warranty with respect to the accuracy of this information or the suitability of these recommendations, assumes no liability to any user thereof. It is the responsibility of the user to investigate and understand pertinent sources of information to comply with all laws and procedures applicable to the safe use and handling of the product and to determine the suitability of the product for its intended use.

**SDS06 - Safety Data Sheet**  
**Vitrified Bonded Abrasive Products**

# Vitrified Bonded Abrasive Products

## DANGER



### Hazard statement(s)

H315 Causes skin irritation

H350 May cause cancer by inhalation.

### Precautionary statement(s)

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P264 Wash thoroughly after handling.

P280 Wear protective gloves.

P308 + P313 If exposed or concerned: Get medical attention.

P302+P352 IF ON SKIN: Wash with plenty of water.

P332+P313 If skin irritation occurs: Get medical attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents and container in accordance with local and national regulations.

Radiac Abrasives Inc.

A Tyrolit Company

1015 S. College Avenue

Salem, IL 62881

800-851-1095